

!


70° , 3

(R1-R4).

-1 12



ТАХИОН
ПРОИЗВОДСТВЕННАЯ ФИРМА





-1

.422412.001-01




RU. 46. 16516





.2

:
 -1 ()
 St1 « (1),
 St1.
 -1
 St2 « ()
 St2 « ».
 1.5 15150-69.
 IP 66.
 :
 1. 1 ;
 2. 1 ;
 3. 1 ;
 4. 1 ;
 :
 1. : U~220 ±15%, 50
6
 2. :~220 ±15%, 50
150
 3.- 60° ÷ +50° ;
 4. ()- 30° ÷ +22° ;
+25° ± 3° ;
 5. ()- 30° ÷ +30° ;
 6. ()600 600 210
 7.15
 8. :
 ()
 -1 ()
 (. 1) , :



5.

(. .2-6)

:

2.

S1.

X2.

S2

1 (

)

« ».

(St1 St2.

« » 0°

« » -10°

-3° ,

-13° ,

-4°

»,

t₁

t₁ +6° .

t₂

t₁

t₂

« » « -

1 2:

t₁ < t₁ < t₁ , t₁ -

t₁ = t₁ -3° ;

t₁ = t₁ +6° , t₁ -

t₁ = t₁ -3° ;

t₁ = t₁ +6° ,

1.

2.

St1	t ₁	t ₂
« -30 » (t ₁ . .)	-33	-24
-30	-33	-24
-25	-28	-19
-20	-23	-14
-15	-18	-9
-10	-13	-4
-5	-8	1
0	-3	6
+5	2	11
+10	7	16

St1

St2	t ₁	t ₂
« -30 » (t ₁ . .)	-33	-24
-30	-33	-24
-25	-28	-19
-20	-23	-14
-15	-18	-9
-10	-13	-4
-5	-8	1
0	-3	6
+5	2	11
+10	7	16

+25° ± 3°

8, 9 10 -

+15° ± 5° .